

Hiab Multilift XR 7S

XR Light Range Hooklifts



The new giant of small hooklifts

The new member of our XR family turns your 10-12 tonne GVW truck into a real multitasking vehicle. The Hiab Multilift XR 7S lets you give your light commercial vehicle extra tasks – just swap the body and go!

Easy control and smooth movements

The Hiab Multilift XR 7S utilises a low hook height of 930 mm and offers great lifting performance with full functionality for mounting and demounting the body and for tipping. Easy control and smooth movements make transporting machinery child's play. Tipping goods is also simple because fast and reliable operation is a guaranteed feature.

Increased versatility and larger payloads

We used the latest 3D-CAD methods and modern production technology to design and manufacture this new range, which minimised the welding needed in construction and resulted in a stronger structure. The exceptional low weight / high strength ratio enables larger payloads, enhances the versatility of the vehicle and maximises its rentability.

Safety the priority

As in all Hiab Multilift demountables, safety is a key priority in the XR-series. Safety features include load-holding valves directly on the cylinders and a tipping lock mechanism. The XR-series meets all the minimum requirements of the EU's Directive on the Safety of Machinery.

TECHNICAL DATA

TYPE	XR 7S		
CAPACITY (kg)	7,000		
GVW OF THE VEHICLE (t)	10 / 12		
CONTAINER LENGTH (internal) (m)	3.0 - 4.0	3.5 - 4.5	4.0 - 5.0
G-LENGTH (mm)	3250	3650	4150
EQUIPMENT WEIGHT (kg)	930	960	990
TIPPING ANGLE (°)	50		
HOOK HEIGHT (mm)	900 / 930		
BODY LEVEL (mm)	220		
MAX. OPERATING PRESSURE (MPa)	30		
RECOMMENDED OIL FLOW (l/min)	35		



We reserve the rights for modifications. Illustrations do not always show an equipment in standard version.

Cargotec improves the efficiency of cargo flows on land and at sea – wherever cargo is on the move. Cargotec's daughter brands Hiab, Kalmar and MacGregor are recognised leaders in cargo and load handling solutions around the world. Cargotec's global network is positioned close to customers and offers extensive services that ensure the continuous, reliable and sustainable performance of equipment. www.cargotec.com



Cargotec Finland Oy
 Nesteentie 36, P.O.Box 39
 FI-21201 Raisio, Finland
 tel. +358 204 55 2399
 fax +358 204 55 2231
www.hiab.com